



701
Hydraulic
 EN 856 4SP



# Part Number	Hose I.D		Hose R.O.D	Hose O.D	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
701MSHA-6	3/8	9.5	17.5	21.4	6500	45.0	7.0	180	0.48	0.71
701MSHA-8	1/2	12.7	20.2	24.6	6000	41.5	9.0	230	0.60	0.90
701MSHA-10	5/8	15.9	23.8	28.0	5000	35.0	10.0	250	0.77	1.15
701MSHA-12	3/4	19.0	28.2	32.0	5000	35.0	11.8	300	1.04	1.55
701MSHA-16	1	25.4	35.3	39.5	4000	27.5	13.3	340	1.40	2.08

* Impulse test conducted with Parker Fittings.

Application : Petroleum base hydraulic fluids and lubricating oils.

Inner Tube : Synthetic rubber.

Reinforcement : Four spiral steel wire.

Cover : Synthetic rubber.

Temp. Range : -40°F to +212°F (-40°C to +100°C)

Impulse Test :

Specified - 4,00,000 cycles.
 Tested upto - 8,00,000 cycles.

Distributor



KB&T

KB& TRADERS

79/1, APS Complex, Iduvampalayam Road,
 Periyandipalayam Tiruppur-641687, India
 Mobile: 90477 77573, Tel : 0421 4955647
 Email: sales@kbandtraders.com.
 Web: www.kbandtraders.com