



KB&T

421SN

Hydraulic

EN 853 1SN / SAE 100 R1 AT



# Part Number	Hose I.D.		Hose R.O.D. mm	Hose O.D. mm	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm			psi	MPa	inch	mm	lbs/ft	kg/m
421SNMSHA-4	1/4	6.4	11.1	13.4	3265	22.5	2.0	50	0.15	0.23
421SNMSHA-5	5/16	7.9	12.7	15.0	3120	21.5	2.3	58	0.18	0.27
421SNMSHA-6	3/8	9.5	15.1	17.4	2610	18.0	2.5	65	0.22	0.33
421SNMSHA-8	1/2	12.7	18.2	20.7	2320	16.0	3.5	90	0.30	0.44
421SNMSHA-10	5/8	15.9	21.4	23.9	1890	13.0	4.0	100	0.34	0.50
421SNMSHA-12	3/4	19.0	25.4	27.8	1525	10.5	4.8	120	0.46	0.68
421SNMSHA-16	1	25.4	33.3	35.8	1275	8.8	6.0	150	0.63	0.94
421SNMSHA-20	1-1/4	31.8	41.8	44.8	915	6.3	16.5	420	0.97	1.44
421SNMSHA-24	1-1/2	38.1	46.4	51.0	725	5.0	20.0	500	1.07	1.59
421SNMSHA-32	2	50.8	59.5	64.5	580	4.0	25.0	630	1.51	2.25

* Impulse test conducted with Parker Fittings.

* All hoses upto-16 have passed 1,50,000 cycles impulse test at half the Min. bend radius "

Application : Petroleum base hydraulic fluids and lubricating oils.

Inner Tube : Synthetic Rubber
Reinforcement : One braid steel wire.

Cover : Synthetic Rubber.

Temp. Range : -40°F to +212°F
(-40°C to +100°C)

Impulse Cycles :

Specified - 1,50,000 cycles.

Tested upto - 3,00,000 cycles.



KB&T

KB& TRADERS

79/1, APS Complex, Iduvampalayam Road,
Periyandipalayam Tiruppur-641687, India
Mobile: 90477 77573, Tel : 0421 4955647
Email: sales@kbandtraders.com.
Web: www.kbandtraders.com