



721
Hydraulic
 EN 856 R12



# Part Number	Hose I.D.		Hose R.O.D	Hose O.D	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
721MSHA-6	3/8	9.5	17.2	20.0	4000	28.0	2.5	65	0.47	0.70
721MSHA-8	1/2	12.7	20.7	24.0	4000	28.0	3.5	90	0.56	0.84
721MSHA-10	5/8	15.9	24.6	27.2	4000	28.0	4.0	100	0.70	1.04
721MSHA-12	3/4	19.0	27.7	31.0	4000	28.0	4.7	120	0.94	1.40
721MSHA-16	1	25.4	34.9	38.0	4000	28.0	6.0	150	1.28	1.90
721MSHA-20	1-1/4	31.8	43.9	46.2	3000	21.0	8.2	210	1.68	2.50
721MSHA-24	1-1/2	38.1	50.4	53.3	2500	17.5	10.0	250	1.93	2.87
721PMMSHA-32PM*	2	50.8	63.6	65.9	2500	17.5	25.0	635	2.76	4.10

Application : Petroleum base hydraulic fluids, and lubricating oils.

Inner Tube : Synthetic rubber.

Reinforcement : Four spiral steel wire.

Cover : Synthetic rubber.

Temp. Range: -40°F to +257°F (-40°C to +125°C)

Impulse Test :

Specified - 5,00,000 cycles.
 Tested upto - 10,00,000 cycles.

* Under validation with Parker fittings / specification

* Impulse test conducted with Parker Fittings.

Distributor



KB&T

KB& TRADERS

79/1, APS Complex, Iduvampalayam Road,
 Periyandipalayam Tiruppur-641687, India
 Mobile: 90477 77573, Tel : 0421 4955647
 Email: sales@kbandtraders.com.
 Web: www.kbandtraders.com