



781
Hydraulic
 EN 856 R13



# Part Number	Hose I.D.		Hose R.O.D	Hose O.D	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
781MSHA-12	3/4	19.0	29.0	31.9	5000	35.0	9.5	240	1.04	1.55
781MSHA-16	1	25.4	35.6	38.5	5000	35.0	12.0	300	1.40	2.08
781MSHA-20	1-1/4	31.8	46.8	50.0	5000	35.0	16.5	420	2.59	3.85
781MSHA-24	1-1/2	38.1	54.3	57.6	5000	35.0	20.0	500	3.23	4.81
781PMMSHA-32PM*	2	50.8	68.1	70.9	5000	35.0	25.0	630	4.48	6.67

* Under validation with Parker fittings / specification

* Impulse test conducted with Parker Fittings.

Application : Petroleum base hydraulic fluids and lubricating oils.

Inner Tube : Synthetic rubber.

Reinforcement : Four or Six spiral steel wire.

Cover : Synthetic rubber .

Temp. Range: -40°F to +257°F (-40°C to +125°C)

Impulse Test :
 Specified - 5,00,000 cycles.
 Tested upto - 10,00,000 cycles.

Distributor



KB&T

KB& TRADERS

79/1, APS Complex, Iduvampalayam Road,
 Periyandipalayam Tiruppur-641687, India
 Mobile: 90477 77573, Tel : 0421 4955647
 Email: sales@kbandtraders.com.
 Web: www.kbandtraders.com