



SPIRAFLEX

Hydraulic
SAE 100 R15



# Part Number	Hose I.D.		Hose R.O.D	Hose O.D	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
792MSHA-12	3/4	19.0	28.4	32.0	6000	41.4	10.5	267	1.08	1.60
792PMMSHA-16PM	1	25.4	35.2	38.5	6000	41.4	13.0	330	1.41	2.10
792PMMSHA-20PM	1-1/4	31.8	46.8	49.6	6000	41.4	17.5	445	2.62	3.90
792PMMSHA-24PM	1-1/2	38.1	54.3	57.1	6000	41.4	21.0	533	3.43	5.11

Application : Extremely high pressure, heavy duty, high impulse hydraulics

Inner Tube : Oil resistant Synthetic rubber.

Reinforcement : Four or Six high tensile steel wire spirals

Cover : Synthetic rubber.

Temp. Range : -40°F to +212°F continuous + 249°F Intermittent (-40°C to +100°C) continuous + 121°C Intermittent

Impulse Test :

Specified - 5,00,000 cycles.
Tested upto - 10,00,000 cycles.

Distributor



KB&T

KB& TRADERS

79/1, APS Complex, Iduvampalayam Road,
Periyandipalayam Tiruppur-641687, India
Mobile: 90477 77573, Tel : 0421 4955647
Email: sales@kbandtraders.com.
Web: www.kbandtraders.com