








EN 854 R3 Hydraulic



# Part Number									
	inch	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
601PM-4PM	1/4	6.4	14.3	1250	8.6	3.0	76	0.11	0.17
601PM-5PM	5/16	7.9	17.5	1200	8.3	4.0	102	0.16	0.24
601PM-6PM	3/8	9.5	19.0	1125	7.8	4.0	102	0.19	0.28
601PM-8PM	1/2	12.7	23.8	1000	6.9	5.0	127	0.32	0.47
601PM-10PM	5/8	15.9	27.0	875	6.0	5.5	140	0.37	0.55
601PM-12PM	3/4	19.0	31.8	750	5.2	6.0	152	0.42	0.63
601PM-16PM	1	25.4	38.1	565	3.9	8.0	203	0.57	0.85
601PM-20PM	1-1/4	31.8	44.5	375	2.6	10.0	254	0.74	1.10
601PM-24PM	1-1/2	38.1	50.8	250	1.7	12.0	306	0.82	1.22
601PM-32PM	2	50.8	64.0	215	1.5	16.1	410	0.91	1.35

Application : Petroleum base hydraulic fluids and lubricating oils.

Inner Tube : Synthetic rubber.

Reinforcement : Two fiber braids.

Cover : Synthetic rubber.

Temp. Range : -40°F to +212°F
(-40°C to +100°C)

Distributor



KB&T

KB& TRADERS

79/1, APS Complex, Iduvampalayam Road,
Periyandipalayam Tiruppur-641687, India
Mobile: 90477 77573, Tel : 0421 4955647
Email: sales@kbandtraders.com.
Web: www.kbandtraders.com