



## SAE 100R4

Hydraulic

Suction and Return line



# Part Number	Hose I.D.		Hose O.D.	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
881PM-12PM	3/4	19.0	29.0	305	2.1	1.6	40	0.32	0.49
881PM-16PM	1	25.4	35.0	250	1.7	2.2	55	0.42	0.62
881PM-20PM	1-1/4	31.8	42.0	205	1.4	2.8	70	0.53	0.79
881PM-24PM	1-1/2	38.0	50.0	145	1.0	3.2	80	0.75	1.12
881PM-32PM	2	50.8	62.0	145	1.0	3.9	100	0.89	1.33
881PM-40PM	2-1/2	63.5	75.0	145	1.0	6.7	170	-	-
881PM-48PM	3	76.2	88.0	145	1.0	8.9	225	-	-

**Application :** Petroleum base hydraulic fluids and lubricating oils.  
**Inner Tube :** Synthetic rubber.  
**Reinforcement :** Multiple layers of fiber braid and one helical wire.  
**Cover :** Synthetic rubber.  
**Temp. Range:** -40° F to +212° F (-40°C to +100°C)

Distributor



KB&T

KB& TRADERS

79/1, APS Complex, Iduvampalayam Road,  
 Periyandipalayam Tiruppur-641687, India  
 Mobile: 90477 77573, Tel : 0421 4955647  
 Email: sales@kbandtraders.com.  
 Web: www.kbandtraders.com