



EN 854 R6 / SAE100R6 Hydraulic



# Part Number	Hose I.D		Hose O.D	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	psi	MPa	inch	mm	lbs/ft	kg/m
SAE100R6PM-4PM	1/4	6.4	12.7	400	2.8	2.5	64	0.09	0.13
SAE100R6PM-5PM	5/16	7.9	14.3	400	2.8	3.0	76	0.11	0.16
SAE100R6PM-6PM	3/8	9.5	15.9	400	2.8	3.0	76	0.12	0.18
SAE100R6PM-8PM	1/2	12.7	19.8	400	2.8	4.0	102	0.17	0.25
SAE100R6PM-10PM	5/8	15.9	23.0	350	2.4	5.0	127	0.20	0.30
SAE100R6PM-12PM	3/4	19.0	26.6	300	2.1	6.0	152	0.23	0.34
SAE100R6PM-16PM	1	25.4	32.5	190	1.3	9.1	230	0.31	0.46

Application : Low pressure hydraulic oils.

Inner Tube : Synthetic Rubber
Reinforcement : One synthetic textile braid.

Cover : Synthetic Rubber.

Temp. Range : -40°Fto+212°F.
(-40°Cto+100°C.)

Distributor



KB&T

KB& TRADERS

79/1, APS Complex, Iduvampalayam Road,
Periyandipalayam Tiruppur-641687, India
Mobile: 90477 77573, Tel : 0421 4955647
Email: sales@kbandtraders.com.
Web: www.kbandtraders.com