


**MULTI - POINT RTD ASSEMBLY WITH PROTECTION TUBE
(WITH SPRING LOADING ARRANGEMENT)**

RTD17



Reference standard :- IEC - 751.

Special Features :

- ★ Mineral insulation.
- ★ Available in all sheath diameters.
- ★ Mineral insulation enables flexibility and Durability.
- ★ Enclosures in all material - Die cast Aluminium / Cast Iron / SS 304 / SS 316
- ★ Enclosures in all categories (Weatherproof, IP-65 to IP-68, Flameproof Gr. IIA, IIB, and Explosionproof, Gr. IIA, IIB, IIC for Hservice application.)

Application :

These assemblies are find application in Refinery & Petrochemical plants which includes catalytic crackers, lime kilns, distillation columns & pressurised reactor vessels.

How to Order:

- | Code | No of Element |
|------|---------------|
| S | Simplex |
| D | Duplex |
- 1
- | Code | Element Type |
|---------|--------------|
| Pt -100 | Pt - 100 RTD |
- 2
- | Code | Range |
|------|-------------------|
| DST | -200°C till 449°C |
| NST | 450°C till 600°C |
- 3
- | Code | Accuracy |
|------|--------------------------------------|
| A | Class 'A' Tolerance as per IEC - 751 |
| B | Class 'B' Tolerance as per IEC - 751 |
- 4
- | Code | No of Point |
|-----------------------|-------------|
| 2 | 2 RTD |
| 3 | 3 RTD |
| 4 | 4 RTD |
| 5 | 5 RTD |
| 6 | 6 RTD |
| 9 | 9 RTD |
| 12 | 12 RTD |
| Other, Please Specify | |
- 5
- | Code | Wire Configuration |
|------|--------------------|
| 2W | 2 Wire System |
| 3W | 3 Wire System |
| 4W | 4 Wire System |
- 6
- | Code | Sheath Diameter |
|---------------------------------|-----------------|
| 3 | 3.0 mm |
| 4.5 | 4.5 mm |
| 6 | 6.0 mm |
| Consult factory for other size. | |
- 7

MULTI - POINT RTD ASSEMBLY WITH PROTECTION TUBE (WITH SPRING LOADING ARRANGEMENT)

RTD17

Code	Sheath Material
S6	SS 316

8

Code	T/W Insertion Length "U"mm
U	Specify in mm.

17

Code	Junction box Type
JWP	Junction box, weatherproof, IP-65 in die-cast Aluminium
JFP	Junction box, flamerproof Gr. IIA IIB in die-cast Aluminium
JEP	Junction box, explosionproof Gr.IIC in die-cast Aluminium
BWP	Weatherproof Head, IP-65 in die-cast Aluminium with cover fitted with two screws.

9

Code	RTD Insertion Length
U1	Specify in mm.
U2	Specify in mm.
U3	Specify in mm.
U4	Specify in mm.
	Etc.

18

Code	No. Of Conduit Entry/Entries
1	One
2	Two
4	Four
6	Six
	Other, Please Specify

10

Code	T/W Extension Length "T"mm
T	Specify in mm.

19

Code	Conduit Entry Size
A	3/4" ET(F)
B	1/2"NPT(F)
C	3/4"NPT(F)
	Other, Please Specify

11

Code	Junction Box Extension Length "N"mm
N	Specify in mm.

20

Code	Junction Box Extension Type
NU	Junction Box With Nipple & Union
F	Junction Box With Flexhose

12

Code	Option Description
0	None
3	Junction Box in SS 304
4	Junction Box in SS 316
7	D.C. cable gland in nickel plated brass
9	D.C. cable gland in SS 304
12	D.C. cable gland in SS 316
16	Junction Box Extension in SS 304
17	Junction Box Extension in SS 316
20	Plug for conduit entry in Carbon Steel [ASTM A105]
21	Plug for conduit entry in SS 304
22	Plug for conduit entry in SS 316
23	Plug for conduit entry in Aluminium
PW	Five Point Factory Calibration Certificate
SX	SS Tag Plate

21

Code	Protecting Tube Material
316	SS 316

13

Code	Protecting Tube		
	Size	OD in mm	Thickness in mm
N40	1/2"Sch.40	21.3	2.77
N80	1/2"Sch.80	21.3	3.74
R40	1"Sch.40	33.4	3.4
R80	1"Sch.80	33.4	4.5
T40	1.5"Sch.40	48.3	3.7
T80	1.5"Sch.80	48.3	5.1
U40	2"Sch.40	60.3	3.9
U80	2"Sch.80	60.3	5.5
	Other, Please Specify		

14

Code	Flange Material
A105	ASTM A105 (CS)
F316	A182 F316
	Consult factory for other material.

15

Code	Flange Type / Size
FF	Fixed Flange (Specify Size)

16

(Ordering Example)

RTD17 | s | (Pt-100) | DST | B | 4 | 3W | 3 | S6 | JWP | 4 | A | NU | 316 | R40 | F316 | FF(2"150#RF) | U=2000 | U1=1800

1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18

T=150 | N=200 | 7

19 | 20 | 21

U4=1200
U3=1400
U2=1600
U1=1800

Distributor



KB&T
KB & TRADERS

79/1, APS Complex, Iduvampalayam Road,
Periyandipalayam Tiruppur-641687, India
Mobile: 90477 77573, Tel : 0421 4955647
Email: sales@kbandtraders.com.
Web: www.kbandtraders.com

